9001SKY203

30mm push button, Type SK, control station, START and STOP, 6A inductive at 120VAC, lock out on STOP, NEMA 4, 4X





Main

IVIAIII	
Range of Product	Harmony 9001KY
Product or Component Type	Control station
Device short name	9001SK
Provided equipment	Label plate START-STOP
Contact block name	KA1 KA3

Complementary

Enclosure/cubicle description	Wall-mounted enclosure 2 cut-outs	
Enclosure material	Polymeric	
Type of Installation	Indoor/outdoor	
Control station composition	2 push-buttons 1 NO + 2 NC	
Connector Type	Screw clamp connector	
[Ue] rated operational voltage	600 V	
[le] rated operational current AC	10 A	

Environment

NEMA Degree of Protection	NEMA 4	
	NEMA 3	
	NEMA 1	
	NEMA 13	
Environmental characteristic	Resistant against immersion in water	
	Dust and oil resistant	
Product Certifications	CSA LR25490 class 3211 03	
	CE	
	UL listed file E42259 CCN NKCR	
Ambient Air Temperature for Operation	-13140 °F (-2560 °C)	
Ambient Air Temperature for Storage	-40158 °F (-4070 °C)	

Ordering and shipping details

Category	21429-9001 SK,SKY	_
Discount Schedule	CS1	
GTIN	785901044604	
Nbr. of units in pkg.	1	
Package weight(Lbs)	34.56 oz (979.76 g)	
Returnability	No	
Country of origin	MX	

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	10.16 in (25.806 cm)
Package 1 width	4.00 in (10.16 cm)
Package 1 Length	25.81 in (65.548 cm)

Offer Sustainability

Green Premium product
WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Yes
Yes
€
China RoHS Declaration
Product Environmental Profile

Contractual warranty

Contracted warranty	
Warranty	18 months