



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 1191.8 MHz SMD 3.8x3.8 mm (BW=55 MHz)

TST Part No.: TA1924A

Customer Part No.: _____

Customer signature required
Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Bruno Huang *Bruno Huang*

Approved by: _____ Kazuma Lee *Kazuma Lee*

Date: _____ 2022/02/11

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.

SAW Filter 1191.8 MHz

MODEL NO.:TA1924A

REV. NO.:3.0




A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3 V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +85°C
5. Moisture Sensitivity Level: Level 1(MSL1)



Electrostatic Sensitive Device
B. ELECTRICAL CHARACTERISTICS:

Item	Unit	Min.	Typical	Max.
Center frequency Fc	MHz	-	1191.8	-
Insertion loss (1164.3~1219.3 MHz) IL	dB	-	2.4	4.0
Amplitude Ripple (1169.8~1213.8 MHz)	dB	-	0.7	1.2
Group delay ripple (1164.3~1219.3 MHz)	ns	-	18	50
Attenuation (Reference level from 0 dB)				
10 ~ 1040 MHz	dB	37	40	-
1040 ~ 1126 MHz	dB	20	33	-
1256 ~ 1345 MHz	dB	20	32	-
1345 ~ 1650 MHz	dB	27	30	-
1650 ~ 3000 MHz	dB	25	28	-
Temperature coefficient of frequency	ppm/k	-	-36	-


C. Frequency Characteristics:



D. OUTLINE DRAWING:



All tolerances are +/-0.05 mm unless otherwise specified
Unit : mm



- 2: Input**
- 6: Output**
- 1, 3, 4, 5, 7, 8: Ground**
- △ : Year Code**
- : Date Code**
- Unit: mm**

△Product / Year Code- 2year cycle


Year	2019	2020
	2021	2022
	2023	2024
Product Code	A	a

Date Code Table:


WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

E. MEASUREMENT CIRCUIT:

HP Network analyzer



F. PCB Footprint:



H. ECOMMENDED REFLOW PROFILE:

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (20~40sec).
4. Time: 2 times.

