


## Power MOSFET

PRODUCT SUMMARY		
V <sub>DS</sub> (V)	100	
R <sub>DS(on)</sub> (Ω)	V <sub>GS</sub> = 10 V	0.077
Q <sub>g</sub> (Max.) (nC)		72
Q <sub>gs</sub> (nC)		11
Q <sub>gd</sub> (nC)		32
Configuration		Single



### FEATURES

- Halogen-free According to IEC 61249-2-21 Definition
- Surface Mount
- Available in Tape and Reel
- Dynamic dV/dt Rating
- Repetitive Avalanche Rated
- 175 °C Operating Temperature
- Fast Switching
- Ease of Parallelizing
- Compliant to RoHS Directive 2002/95/EC



### DESCRIPTION

Third generation Power MOSFETs from Vishay provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The D²PAK (TO-263) is a surface mount power package capable of accommodating die size up to HEX-4. It provides the highest power capability and the lowest possible on-resistance in any existing surface mount package. The D²PAK (TO-263) is suitable for high current applications because of its low internal connection resistance and can dissipate up to 2.0 W in a typical surface mount application.

### ORDERING INFORMATION

Package	D²PAK (TO-263)	D²PAK (TO-263)	D²PAK (TO-263)
Lead (Pb)-free and Halogen-free	SiHF540S-GE3	SiHF540STR-GE3 <sup>a</sup>	SiHF540STRR-GE3 <sup>a</sup>
Lead (Pb)-free	IRF540SPbF	IRF540STRLPbF <sup>a</sup>	IRF540STRRPbF <sup>a</sup>
	SIHF540S-E3	SIHF540STL-E3 <sup>a</sup>	SIHF540STR-E3 <sup>a</sup>
SnPb	IRF540S	IRF540STRL <sup>a</sup>	IRF540STRR <sup>a</sup>
	SIHF540S	SIHF540STL <sup>a</sup>	SIHF540STR <sup>a</sup>

#### Note

a. See device orientation.

### ABSOLUTE MAXIMUM RATINGS T<sub>C</sub> = 25 °C, unless otherwise noted

PARAMETER	SYMBOL	LIMIT	UNIT
Drain-Source Voltage	V <sub>DS</sub>	100	V
Gate-Source Voltage	V <sub>GS</sub>	± 20	
Continuous Drain Current	V <sub>GS</sub> at 10 V	28	A
		20	
Pulsed Drain Current <sup>a</sup>	I <sub>DM</sub>	110	
Linear Derating Factor		1.0	W/°C
Linear Derating Factor (PCB Mount) <sup>e</sup>		0.025	
Single Pulse Avalanche Energy <sup>b</sup>	E <sub>AS</sub>	230	mJ
Avalanche Current <sup>a</sup>	I <sub>AR</sub>	28	A
Repetitive Avalanche Energy <sup>a</sup>	E <sub>AR</sub>	15	mJ
Maximum Power Dissipation	T <sub>C</sub> = 25 °C	150	W
Maximum Power Dissipation (PCB Mount) <sup>e</sup>		3.7	
Peak Diode Recovery dV/dt <sup>c</sup>	dV/dt	5.5	V/ns
Operating Junction and Storage Temperature Range	T <sub>J</sub> , T <sub>stg</sub>	- 55 to + 175	°C
Soldering Recommendations (Peak Temperature)	for 10 s	300 <sup>d</sup>	

#### Notes

- Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).
- V<sub>DD</sub> = 25 V, starting T<sub>J</sub> = 25 °C, L = 440 µH, R<sub>g</sub> = 25 Ω, I<sub>AS</sub> = 28 A (see fig. 12).
- I<sub>SD</sub> ≤ 28 A, dI/dt ≤ 170 A/µs, V<sub>DD</sub> ≤ V<sub>DS</sub>, T<sub>J</sub> ≤ 175 °C.
- 1.6 mm from case.
- When mounted on 1" square PCB (FR-4 or G-10 material).

\* Pb containing terminations are not RoHS compliant, exemptions may apply

**THERMAL RESISTANCE RATINGS**

PARAMETER	SYMBOL	TYP.	MAX.	UNIT
Maximum Junction-to-Ambient	$R_{thJA}$	-	62	$^{\circ}\text{C}/\text{W}$
Maximum Junction-to-Ambient (PCB Mount) <sup>a</sup>	$R_{thJA}$	-	40	
Maximum Junction-to-Case (Drain)	$R_{thJC}$	-	1.0	

**Note**

a. When mounted on 1" square PCB (FR-4 or G-10 material).





**SPECIFICATIONS**  $T_J = 25 \text{ }^{\circ}\text{C}$ , unless otherwise noted

PARAMETER	SYMBOL	TEST CONDITIONS		MIN.	TYP.	MAX.	UNIT	
<b>Static</b>								
Drain-Source Breakdown Voltage	$V_{DS}$	$V_{GS} = 0 \text{ V}, I_D = 250 \mu\text{A}$		100	-	-	V	
$V_{DS}$ Temperature Coefficient	$\Delta V_{DS}/T_J$	Reference to $25 \text{ }^{\circ}\text{C}$ , $I_D = 1 \text{ mA}$		-	0.13	-	$^{\circ}\text{C}/\text{V}$	
Gate-Source Threshold Voltage	$V_{GS(th)}$	$V_{DS} = V_{GS}, I_D = 250 \mu\text{A}$		2.0	-	4.0	V	
Gate-Source Leakage	$I_{GSS}$	$V_{GS} = \pm 20 \text{ V}$		-	-	$\pm 100$	nA	
Zero Gate Voltage Drain Current	$I_{DSS}$	$V_{DS} = 100 \text{ V}, V_{GS} = 0 \text{ V}$		-	-	25	$\mu\text{A}$	
		$V_{DS} = 80 \text{ V}, V_{GS} = 0 \text{ V}, T_J = 150 \text{ }^{\circ}\text{C}$		-	-	250		
Drain-Source On-State Resistance	$R_{DS(on)}$	$V_{GS} = 10 \text{ V}$	$I_D = 17 \text{ A}^b$	-	-	0.077	$\Omega$	
Forward Transconductance	$g_{fs}$	$V_{DS} = 50 \text{ V}, I_D = 17 \text{ A}^b$		8.7	-	-	S	
<b>Dynamic</b>								
Input Capacitance	$C_{iss}$	$V_{GS} = 0 \text{ V}, V_{DS} = 25 \text{ V}, f = 1.0 \text{ MHz}$ , see fig. 5		-	1700	-	pF	
Output Capacitance	$C_{oss}$			-	560	-		
Reverse Transfer Capacitance	$C_{rss}$			-	120	-		
Total Gate Charge	$Q_g$	$V_{GS} = 10 \text{ V}$	$I_D = 17 \text{ A}, V_{DS} = 80 \text{ V}$ , see fig. 6 and 13 <sup>b</sup>	-	-	72	nC	
Gate-Source Charge	$Q_{gs}$			-	-	11		
Gate-Drain Charge	$Q_{gd}$			-	-	32		
Turn-On Delay Time	$t_{d(on)}$			-	11	-		
Rise Time	$t_r$	$V_{DD} = 50 \text{ V}, I_D = 17 \text{ A}, R_g = 9.1 \Omega, R_D = 2.9 \Omega$ , see fig. 10 <sup>b</sup>		-	44	-	ns	
Turn-Off Delay Time	$t_{d(off)}$			-	53	-		
Fall Time	$t_f$			-	43	-		
Internal Drain Inductance	$L_D$			-	4.5	-	nH	
Internal Source Inductance	$L_S$	Between lead, 6 mm (0.25") from package and center of die contact		-	7.5	-		
<b>Drain-Source Body Diode Characteristics</b>								
Continuous Source-Drain Diode Current	$I_S$	MOSFET symbol showing the integral reverse p - n junction diode		-	-	28	A	
Pulsed Diode Forward Current <sup>a</sup>	$I_{SM}$			-	-	110		
Body Diode Voltage	$V_{SD}$	$T_J = 25 \text{ }^{\circ}\text{C}, I_S = 28 \text{ A}, V_{GS} = 0 \text{ V}^b$		-	-	2.5	V	
Body Diode Reverse Recovery Time	$t_{rr}$	$T_J = 25 \text{ }^{\circ}\text{C}, I_F = 17 \text{ A}, dI/dt = 100 \text{ A}/\mu\text{s}^b$		-	180	360	ns	
Body Diode Reverse Recovery Charge	$Q_{rr}$			-	1.3	2.8	$\mu\text{C}$	
Forward Turn-On Time	$t_{on}$	Intrinsic turn-on time is negligible (turn-on is dominated by $L_S$ and $L_D$ )						

**Notes**

a. Repetitive rating; pulse width limited by maximum junction temperature (see fig. 11).

b. Pulse width  $\leq 300 \mu\text{s}$ ; duty cycle  $\leq 2 \%$ .

**TYPICAL CHARACTERISTICS** 25 °C, unless otherwise noted

**Fig. 1 - Typical Output Characteristics,  $T_C = 25$  °C**

**Fig. 3 - Typical Transfer Characteristics**

**Fig. 2 - Typical Output Characteristics,  $T_C = 175$  °C**

**Fig. 4 - Normalized On-Resistance vs. Temperature**





Fig. 5 - Typical Capacitance vs. Drain-to-Source Voltage

Fig. 7 - Typical Source-Drain Diode Forward Voltage









Fig. 6 - Typical Gate Charge vs. Gate-to-Source Voltage

Fig. 8 - Maximum Safe Operating Area


**Fig. 9 - Maximum Drain Current vs. Case Temperature**

**Fig. 10a - Switching Time Test Circuit**

**Fig. 10b - Switching Time Waveforms**

**Fig. 11 - Maximum Effective Transient Thermal Impedance, Junction-to-Case**




Fig. 12a - Unclamped Inductive Test Circuit




Fig. 12b - Unclamped Inductive Waveforms




Fig. 12c - Maximum Avalanche Energy vs. Drain Current




Fig. 13a - Basic Gate Charge Waveform






Fig. 13b - Gate Charge Test Circuit

**Peak Diode Recovery dV/dt Test Circuit**

**Note**

a.  $V_{GS} = 5$  V for logic level devices

**Fig. 14 - For N-Channel**

Vishay Siliconix maintains worldwide manufacturing capability. Products may be manufactured at one of several qualified locations. Reliability data for Silicon Technology and Package Reliability represent a composite of all qualified locations. For related documents such as package/tape drawings, part marking, and reliability data, see [www.vishay.com/ppg?91022](http://www.vishay.com/ppg?91022).



### Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.