

<u>Ultra Series</u>

UB-09-628-S(F)



More Information





Specifications

Mounting Panel Mount

Operating Mode Ultra Loud Fast Beep Tone

 Operating Voltage
 6-28 Vdc

 Operating Frequency
 2100±250 Hz

 Typical Operating Current
 20 mA at 6 Vdc

 50 mA at 28 Vdc

Typical Sound Pressure $93 \pm 5 \text{ dB(A)}$ at 6 Vdc at 24 inches (61 cm), at 25°C $109 \pm 5 \text{ dB(A)}$ at 28 Vdc at 24 inches (61 cm), at 25°C

Termination Quick Connect Blades with Screws

Termination Strength Pull test with a maximum of 22 pounds (10 kg) load

Operating Temperature -20_C to +65_C Storage Temperature -40_C to +85_C

Surge Voltage 20% over maximum rated voltage for less than 5 minutes

Reverse Voltage Protection To the maximum operating voltage

Case- Plastic NORYL N-190, Flame Retardant UL 94-VO, Black

Construction Materials Internal Circuit- Audio-oscillator and piezoelectric driver

Potting- 2 parts epoxy resin or silicone, black

Diaphragm- Stainless Steel 304

Gasket Gasket (sold separately) 0.062" thick, 60 Durometer Neoprene

ASTM B117 Certified - Withstands exposure to salt spray for 300 hours IP 68 Certified - Withstands water submergence and dust exposure Humidity- 95% relative humidity at +40 C continuously for 100 hours.

Vibration- Withstands vibration between 0 and 55 Hz. on all axes.

Life Expectancy 10 years under normal operating conditions.

Warranty For a period of two years from the date of manufacture under normal operating conditions.

Notes This product is not intended as a life safety device.

Terms and Conditions of Sale Link here

Construction Materials

Dimensions

