## PRO-SHIELD<sup>®</sup> 7201

NON-CONDUCTIVE AIR-DRYING LIQUID PRIMER



# Customer Value Proposition:

PRO-SHIELD® 7201 is an air-drying liquid primer used to improve the adhesion of Parker Chomerics PRO-SHIELD conductive paints and coatings to metal and other non-silicone substrates. The primer is moisture reactive and clear in color.



### How To Apply:

1. Surfaces to be joined must be clean, dry and oil free. In a well-ventilated area, clean the substrates with isopropyl alcohol (IPA) and let the solvent flash off. (Other solvents, such as methylethyl-ketone (MEK), toluene, or acetone can be used to clean difficult to remove contaminants).

2. Wet a lint-free cotton cloth with PRO-SHIELD 7201 primer and apply to the surface in horizontal and vertical strokes. Keep the surface wet at all times. A cotton swab is a common applicator for a grooved or stepped surface.

**NOTE**: Due to the low flash point temperature of the primer, ensure that the container is re-sealed immediately after use.

**3.** The primed surface must cure for 30 minutes at room temperature. A relative humidity of 40% to 70% is optimal. A low humidity level may require a longer cure time.

NOTE: There is no elevated temperature cure time for the primer.

4. Apply the PRO-SHIELD adhesive / sealant perproduct instructions.

**NOTE**: If the primer has been applied for more than 4 hours without the application of the adhesive / sealant, repeat steps 1 through 4.

#### **Ordering Information**

Part Number	Packaging	Weight (grams)
90-02-7201-0000	3 dram glass vial	10
90-09-7201-0000	4oz glass bottle	95

WARNING: This product can expose you to TOLUENE, which is known to the State of California to cause birth defects and/or other reproductive harm. For more information go to www.P65Warnings.ca.gov

CHOMERICS and PRO-SHIELD is a registered trademark of Parker Hannifin Corporation. ® 2018

PRO-SHIELD 7201



### ENGINEERING YOUR SUCCESS.

## Contact Information:

Parker Hannifin Corporation Chomerics Division 77 Dragon Ct. Woburn, MA 01801 USA

phone 781 935 4850 fax 781 933 4318 CHOmailbox@parker.com

www.parker.com/chomerics