




## P3M12160K4 SiC MOS N-Channel Enhancement Mode

$V_{RRM}$  = 1200 V  
 $I_D$  = 19 A  
 $I_D$  (100°C) = 13 A  
 $R_{DS(on)}$  = 160 mΩ

## SiC MOS P3M12160K4 N-Channel Enhancement Mode

### Features

- Qualified to AEC-Q101
- High Blocking Voltage with Low On-Resistance
- High-Frequency Operation
- Ultra-Small  $Q_{gd}$
- 100% UIS tested



TO-247-4

Drain	1
Power Source	2
Kelvin Source	3
Gate	4



### Application

- Solar Inverters
- EV Battery Chargers
- High Voltage DC/DC Converters
- Switch Mode Power Supplies

### Order Information

Part number	Package	Marking
P3M12160K4	TO-247-4	P3M12160K4



## **Contents**

Features.....	1
Benefits.....	1
Application.....	1
Order Information .....	1
<b>Contents.....</b>	<b>2</b>
1. Maximum Ratings.....	3
2. Electrical Characteristics .....	4
3. Reverse Diode Characteristics .....	5
4. Thermal Characteristics.....	6
5. Typical Performance .....	6
6. Definitions .....	10
7. Package Outlines.....	11



# P3M12160K4 SiC MOS

## N-Channel Enhancement Mode

### 1. Maximum Ratings

At  $T_J = 25^\circ\text{C}$ , unless specified otherwise

Parameter	Symbol	Value	Unit	Test Conditions
Drain - Source Voltage	$V_{DS\max}$	1200	V	$V_{GS} = 0\text{V}$ $I_D = 100\mu\text{A}$
Gate - Source Voltage (dynamic)	$V_{GS\max}$	-8 / +21	V	AC ( $f > 1\text{Hz}$ )
Gate - Source Voltage (static)	$V_{GSop}$	-3 / +15	V	Static
Continuous Drain Current	$I_D$	19	A	$V_{GS} = 15\text{V}$ $T_C = 25^\circ\text{C}$
		13		$V_{GS} = 15\text{V}$ $T_C = 100^\circ\text{C}$
Power Dissipation	$P_D$	110	W	
Operating Junction	$T_J$	-55 To +175	°C	
Storage Temperature	$T_{stg}$	-55 To +175	°C	
Solder Temperature	$T_L$	260	°C	
Mounting Torque	$M_d$	1 8.8	Nm lbf-in	M3 or 6-32 screw



## 2. Electrical Characteristics

At  $T_J = 25^\circ\text{C}$ , unless specified otherwise

Parameter	Symbol	Value			Unit	Test Conditions
		Min.	Typ.	Max.		
Drain-Source Breakdown Voltage	$V_{(\text{BR})\text{DSS}}$	1200	/	/	V	$V_{GS} = 0\text{V}$ $I_D = 100\mu\text{A}$
Gate Threshold Voltage	$V_{GS(\text{th})}$	1.8	2.4	/	V	(tested after 30ms pulse at $V_{GS} = 15\text{V}$ ) $V_{DS} = V_{GS}$ $I_D = 2.5\text{mA}$ $T_J = 25^\circ\text{C}$
		/	1.6	/	V	$V_{DS} = V_{GS}$ $I_D = 2.5\text{mA}$ $T_J = 175^\circ\text{C}$
Zero Gate Voltage Drain Current	$I_{DSS}$	/	1.8	500	$\mu\text{A}$	$V_{GS} = 0\text{V}$ $V_{DS} = 1200\text{V}$
Gate-Source Leakage Current	$I_{GSS}$	/	20	250	nA	$V_{GS} = 15\text{V}$ $V_{DS} = 0\text{V}$
Drain-Source On-State Resistance	$R_{DS(\text{on})}$	/	160	192	$\text{m}\Omega$	$V_{GS} = 15\text{V}$ $I_D = 10\text{A}$ $T_J = 25^\circ\text{C}$
		/	208	/		$V_{GS} = 15\text{V}$ $I_D = 10\text{A}$ $T_J = 175^\circ\text{C}$
Transconductance	$g_{fs}$	/	5	/	S	$V_{DS} = 20\text{V}$ $I_{DS} = 10\text{A}$ $T_J = 25^\circ\text{C}$
		/	4.8	/		$V_{DS} = 20\text{V}$ $I_{DS} = 10\text{A}$ $T_J = 175^\circ\text{C}$



**P3M12160K4 SiC MOS**  
**N-Channel Enhancement Mode**

Parameter	Symbol	Value			Unit	Test Conditions
		Min.	Typ.	Max.		
Input Capacitance	$C_{iss}$	/	1016	/	pF	$V_{GS} = 0V$ $V_{DS} = 800V$ $f = 1MHz$ $V_{AC} = 25mV$
Output Capacitance	$C_{oss}$	/	36.8	/		
Reverse Transfer Capacitance	$C_{rss}$	/	3.2	/		
Coss Stored Energy	$E_{oss}$	/	26.5	/		
Gate to Source Charge	$Q_{gs}$	/	11.1	/		
Gate to Drain Charge	$Q_{gd}$	/	6.1	/		
Total Gate Charge	$Q_g$	/	27.3	/		

### 3. Reverse Diode Characteristics

At  $T_J = 25^\circ C$ , unless specified otherwise

Parameter	Symbol	Value		Unit	Test Conditions
		Typ.	Max.		
Diode Forward Voltage	$V_{SD}$	5.2	/	V	$V_{GS} = -3V$ $I_{SD} = 5A$ $T_J = 25^\circ C$
		4.8	/		
Continuous Diode Forward Current	$I_S$	13	/	A	$V_{GS} = -3V$



# P3M12160K4 SiC MOS N-Channel Enhancement Mode

## 4. Thermal Characteristics

Parameter	Symbol	Value	Unit
Thermal Resistance from Junction to Case	$R_{\theta JC}$	1.36	°C/W

## 5. Typical Performance

At  $T_J = 25^\circ\text{C}$ , unless specified otherwise




Figure 1. Output Characteristics  $T_J = -55^\circ\text{C}$




Figure 2. Output Characteristics  $T_J = 25^\circ\text{C}$




Figure 3. Output Characteristics  $T_J = 125^\circ\text{C}$




Figure 4. Output Characteristics  $T_J = 175^\circ\text{C}$



# P3M12160K4 SiC MOS N-Channel Enhancement Mode




Figure 5. Normalized On-Resistance vs. Temperature




Figure 6. On-Resistance vs. Drain Current Various Temperatures




Figure 7. On-Resistance vs. Gate-Source Voltage




Figure 8. Transfer Characteristic for Various Junction Temperatures




Figure 9. Body Diode Characteristic at  $-55^\circ\text{C}$










Figure 10. Body Diode Characteristic at  $25^\circ\text{C}$



# P3M12160K4 SiC MOS N-Channel Enhancement Mode





## P3M12160K4 SiC MOS N-Channel Enhancement Mode




Figure 17. 3rd Quadrant Characteristic at 125°C




Figure 18. 3rd Quadrant Characteristic at 175°C




Figure 19. Maximum Power Dissipation Derating vs. Case Temperature




Figure 20. Output Capacitor Stored Energy




Figure 21. Capacitances vs. Drain-Source Voltage (0 - 200V)




Figure 22. Capacitances vs. Drain-Source Voltage (0 - 1000V)



# P3M12160K4 SiC MOS N-Channel Enhancement Mode

## 6. Definitions




Figure 23. Turn-off Transient Definitions




Figure 24. Turn-on Transient Definitions




Figure 25. Reverse Recovery Definitions





Figure 26.  $v_{GS}$  Transient Definitions



# P3M12160K4 SiC MOS N-Channel Enhancement Mode

## 7. Package Outlines



Symbol	Dimensions		
	Min.	Nom.	Max.
A	4.83	5.02	5.21
A1	2.28	2.41	2.54
A2	1.91	2.00	2.16
b <sup>1</sup>	1.07	1.20	1.28
b	1.07	1.20	1.33
b1	2.39	2.67	2.94
b2	2.39	2.67	2.84
b3	1.07	1.30	1.60
b4	1.07	1.30	1.50
b5	2.39	2.53	2.69
b6	2.39	2.53	2.64
c	0.55	0.60	0.68
c1	0.55	0.60	0.65
D	22.30	23.45	23.80
D1	16.25	16.55	17.65
D2	0.95	1.19	1.25
E	15.75	15.94	16.13
E1	13.10	14.02	14.15
E2	3.60	1.10	5.10
E3	1.00	1.45	1.90
E4	12.38	13.26	13.43
e	2.54BSC		
e1	5.08BSC		
L	17.31	17.57	17.82
L1	3.97	4.19	4.37
L2	2.35	2.50	2.65
OP	3.51	3.61	3.65
OP	7.19 REF.		
Q	5.49	5.79	6.00
S	6.04	6.17	6.30

Drawing and Dimensions



## Important Notice

---

The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples, hints or any typical values stated herein and/or any information regarding the application of the product, PN Junction hereby disclaims any and all warranties and liabilities of any kind, including without limitation warranties of non-infringement of intellectual property rights of any third party.

PN Junction reserves the right to make changes at any time to any products or information herein, without notice. "Typical" parameters which may be provided in PN Junction data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typical" must be validated for each customer application by customer's technical experts.

In addition, any information given in this document is subject to customer's compliance with its obligations stated in this document and any applicable legal requirements, norms and standards concerning customer's products and any use of the product of PN Junction in customer's applications. The data contained in this document is exclusively intended for technically trained staff. It is the responsibility of customer's technical departments to evaluate the suitability of the product for the intended application and the completeness of the product information given in this document with respect to such application.

For further information on the product, technology, delivery terms and conditions and prices please contact your nearest PN Junction office ([www.pnjsemi.com](http://www.pnjsemi.com)).

## Warnings

---

Due to technical requirements products may contain dangerous substances. For information on the types in question please contact your nearest PN Junction office.

Except as otherwise explicitly approved by PN Junction in a written document signed by authorized representatives of PN Junction, PN Junction's products may not be used in any applications where a failure of the product or any consequences of the use thereof can reasonably be expected to result in personal injury.