# 9080LBA265202

Power distribution block, Linergy, 2 pole, 2 line, 2 load, 620A CU, 500A AL, 600 V



Main	
Range	9080LB
Product	Power Distribution Block
Current Rating	620 A copper 500 A aluminium

Compl	ement	tary
-------	-------	------

Voltage Rating	600 V AC/DC
Mounting Type	Surface mount
Number of poles	2
Terminals per Pole	2 line 2 load
Wire Size	Line 2, AWG 6350 kcmil, copper or aluminium Load 2, AWG 6350 kcmil, copper or aluminium
Electrical Connection	Tin plated aluminium lugs
SCCR	100 kA UL 508 A
Ambient Air Temperature for Operation	-40302 °F (-40150 °C)
Block Material	Phenolic block
Terminal Tightening Torque	Line lug 275 lbf.in (31.07 N.m) AWG 4350 kcmil copper or aluminium Load lug 275 lbf.in (31.07 N.m) AWG 4350 kcmil copper or aluminium
Wire stripping length	Line 1.06 in (26.92 mm) Load 1.06 in (26.92 mm)
Height	5.5 in (139.70 mm)
Width	5.88 in (149.35 mm)
Depth	3.13 in (79.50 mm)
End Barrier	9080LB52

### Environment

Certifications CSA file 70361 class 6228 01 UL recognized E60616 CCN XCFR2 CE	CE
---	----

#### Ordering and shipping details

21711-9080 LB	
CP1	
785901157052	
1	
2.22 lb(US) (1.007 kg)	
Yes	
US	
	CP1 785901157052 1 2.22 lb(US) (1.007 kg) Yes

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	3.60 in (9.144 cm)
Package 1 width	6.00 in (15.24 cm)
Package 1 Length	8.90 in (22.606 cm)
Unit Type of Package 2	CAR
Number of Units in Package 2	6
Package 2 Weight	14.16 lb(US) (6.423 kg)
Package 2 Height	12.50 in (31.75 cm)
Package 2 width	9.60 in (24.384 cm)
Package 2 Length	13.30 in (33.782 cm)

### Offer Sustainability

WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
☑ REACh Declaration
Yes
Compliant EEU RoHS Declaration
Yes
Yes
€Yes
<sup>™</sup> China RoHS Declaration

# Contractual warranty

Warranty	18 months
varianty	10 months