Harmony eXLhoist, standard, XARS12D18H system with charger, shoulder belt, cable USB/RJ45 and config software



Main

Range of Product	Harmony eXLhoist
Product or Component Type	Control station
Device short name	XARS
Control station type	Wireless
Product Specific Application	Hoisting applications Material handling
Number of Channels	50
Control station application	Stop function SIL 2 maximum can reach PL d/ category 3)EN/IEC 62061 Stop function SIL 2 maximum can reach PL d/ category 3)EN/ISO 13849-1 Emergency stop function SIL 3 maximum can reach PL e/category 4)EN/IEC 62061 Emergency stop function SIL 3 maximum can reach PL e/category 4)EN/ISO 13849-1 Motion function SIL 1 maximum can reach PL c/ category 1)EN/IEC 62061 Motion function SIL 1 maximum can reach PL c/ category 1)EN/ISO 13849-1 Limiter protection function SIL 1 maximum can reach PL c/category 1)EN/IEC 62061 Limiter protection function SIL 1 maximum can reach PL c/category 1)EN/ISO 13849-1

Complementary

Complementary		
Kit composition	Shoulder belt Base station	
	Configuration software Cable	
	Remote control	
Operating distance	100 m in free air	
Connector Type	Industrial socket	_
Cable entry	Cable gland	
Communication network type	Wireless bluetooth low energy	
Transmission frequency	2.4 GHz	

Environment

Radio agreement	ANATEL
radio agreement	SRRC
	ICASA
	ARIB
	FCC
	RSS
Relative humidity	095 % -4113 °F (-2045 °C) storage
·	, , ,
Electromagnetic compatibility	Resistance to electrostatic discharge 4 kV on contact)class B IEC 61000-4-2
	Resistance to electrostatic discharge 8 kV in air)class B IEC 61000-4-2
	Resistance to radiated electromagnetic fields 10 V/mclass B IEC 61000-4-3
Standards	EN/IEC 60204-1 safety
	EN/ISO 13849-1 safety
	EN/IEC 62061 safety
	EN/IEC 61508 safety
	EN/ISO 13850 safety
	EN/IEC 60204-32 hoisting applications
	EN 13557 hoisting applications
	EN 12077-2 hoisting applications
	EN 15011 hoisting applications
	EN 14439 hoisting applications
	EN 14492 hoisting applications
	ETSI EN 301 489-1 radio
	ETSI EN 301 489-3 radio
	ETSI EN 301 489-17 radio
	ETSI EN 300 440-2 radio
	ETSI EN 300 328 radio
	FCC part 15 radio
	RSS GEN issue 3 radio
	RSS 210 issue 8 radio
	ARIB STD-T81 radio
Product certifications	CE
	UL
	CSA
	C-tick
	JIS
	KC
	EAC

Ordering and shipping details

0 11 0	
Category	22479-EXL HOIST WIRELESS PENDANT & ACC
Discount Schedule	CS2
GTIN	3606480662447
Nbr. of units in pkg.	1
Package weight(Lbs)	6.82 lb(US) (3.092 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	7.80 in (19.8 cm)	
Package 1 width	11.22 in (28.5 cm)	
Package 1 Length	12.13 in (30.8 cm)	
Unit Type of Package 2	S04	
Number of Units in Package 2	2	
Package 2 Weight	15.63 lb(US) (7.089 kg)	
Package 2 Height	11.81 in (30 cm)	
Package 2 width	15.75 in (40 cm)	
Package 2 Length	23.62 in (60 cm)	

Offer Sustainability

Onor Odolamability	
California proposition 65	WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	₽¥Yes
China RoHS Regulation	☐ China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.