# Product data sheet Characteristics

# 70-461-1

Socket, Harmony, for 782H 792 relays, 10A, 14 pins, screw clamp terminals, mixed contact





### Main

Range of product	Harmony Electromechanical Relays	
Product or component type	Socket	
Product compatibility	Relay 792XDX relay 782XDXH	
Number of terminals	14	
Switch function	4PDT	
Contacts type and composition	4 C/O	

## Complementary

[ln] rated current	10 A
[Ue] rated operational voltage	300 V
Contact terminal arrangement	Mixed
Connections - terminals	Panel screw clamp terminals, clamping connection capacity:2 x 1.52 x 2.5 m-m², AWG 16AWG 14 solid for output Panel screw clamp terminals, clamping connection capacity:2 x 1.52 x 2.5 m-m², AWG 16AWG 14 stranded for output
Tightening torque	Chassis: 0.8 N.m, AWG 16AWG 14, copper Screw: < 0.8 N.m
Fixing mode	By screws, M3, for panel
Shape of screw head	Combination roundhead
Net weight	50 G
Width	30.7 Mm
Depth	64 Mm

#### **Environment**

Ambient air temperature for storage	-40105 °C
Ambient air temperature for operation	-4070 °C
Flame retardance	UL94-V0
Product certifications	UL CSA CE

# Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	6.9 Cm
Package 1 Width	3.07 Cm
Package 1 Length	2.54 Cm
Package 1 Weight	50 G

## Offer Sustainability

Green Premium product
☑ REACh Declaration
Yes
Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Yes
Yes
China RoHS Declaration
€Yes
Product Environmental Profile
The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Product Life Status : Commercialised